



ASLAN™

★ GYPSUM LLP ★



ABOUT US

Aslan Gypsum LLP is a leading supplier of Imported Gypsum Powder & manufactures GRG (Glass Reinforced Gypsum) fiber Ceiling Tiles, Started in Maharashtra & other states in 2021 "Aslan Gypsum LLP" has earned an outstanding reputation as a supplier of best quality Gypsum Boards, Gypsum Powder, Bonding Agents, and GRG Ceiling Tiles for the construction and building materials industry.

Over the years we have been able to distinguish ourselves as a leading supplier by constantly defining and refining excellence in products, processes, and customer care.

In our zeal to expand our wings and cater to the constant demand from clients, we are engaged in the supply of

- ▶ **Aslan Gypsum** ▶ **Sadaaf Gypsum** ▶ **Aslan Bondit**
- ▶ **Aslan Gypsum Boards** ▶ **GRG Ceiling Tiles**

VISION & MISSION

- ▶ To provide uninterrupted quality, responsive service and competitive pricing.
- ▶ To provide best quality product to the customers as per the requirement.
- ▶ Continue improvement in process and productivity.

Test Report

Sr. No.	Particulars	Parameters	Unit	Test Result
1	Initial Setting Time	8-12	Minutes	13-15
2	Final Setting Time	18-22	Minutes	20-22
3	Colour	White	Brightness	96.5%
4	Dry Bulk Density	770kg/m ³ . Max	KG/m ³	685-710
5	Compressive Strength	15-17	kg/cm ²	100
6	Fineness	105 μm	%	99% (Percent)
9	Approx Coverage per bag (25 kg) on 12 mm Thickness		Sqft.	22-23ft.

Aslan Gypsum Complies with the result of BIS: 2547 Part II- 1976 for Gypsum Building material.

PRODUCT FEATURES

Aslan Bondit

Ready to apply, single coat application Contains fine aggregates to impart better mechanical load, Green in color, easy to identify applied surface Dried in 6 to 8 hours, Plaster can be applied any time cure the drying is complete The only Bonding Agent specified with ASLAN BRAND BOND IT. It can be applied on any low suction concrete surfaces and shear warts, Do not apply on wet surface. Approximate coverage is 5m²/kg

APPLICATION PROCEDURE

- 1) Wash concrete surface with water and allow the surface to dry for 15 minutes.
- 2) Mix the contents before use.
- 3) Apply with roller or brush on dry concrete blocks /RCC.
- 4) Apply gypsum plaster after 4 hours or after the material has dried based on environmental conditions.

USES

Used as a Bonding Agent Eliminates hacking and ensure strong and firm bond of Internal Plaster with substrate surfaces.

Apply this with fine aggregate over union with a paint brush Allow it the dry theory of around 4 to 6 hrs However, this may vary according to the environmental condition and variation.

CAUTION

Wash hands with water after use. Keep away from eye contact, in case of eye contact wash eye thoroughly with water, if imitation persists kindly seek advice from doctor.



AVAILABLE PACKING
1kg, 5kgs, 10kgs & 20 kgs



Application Methodology

- ▶ Always mix powder to water not water to powder (1:1.25 ratio)
- ▶ Before plastering on concrete surface, kindly ensure that any mould / Shuttering oil or other agents present should be removed from the surface.
- ▶ Recommended to pre wet surface before application.
- ▶ Surface should be firm, dry, clean and free from dust.
- ▶ The hole and cracks on the surface should be repaired in advance.
- ▶ In case of hacking it should be 40-50 numbers per square feet area up to 3-5 mm depth.

Our Prestigious Project



Kundan Espacio - Balewadi



Kundan Peak - NIBM



Rahul Aston - Hinjewadi



Happiness Hub - Shivapur



Paranjape Madhukosh- Dhayari



Abhiruchi Parisar - Narhe

Many Commercial & Residential
Projects are going on



Marketed By:
ASLAN GYPSUM LLP
SR NO 655/10/5 Ganga Dham Kondhwa Road
NR Shreeji Pune City Pune (CB) 411037
Contact No. : +91 992 349 1549 / 976 365 1901
Email: gypsumaslan@gmail.com
Website: www.aslangypsum.com